

Revision Date 04/29/2015

1. Identification

Product name Sikadur AnchorFix®-1 Part B

Supplier Sika Corporation

Address 201 Polito Avenue

Lyndhurst, NJ 07071

USA

www.sikausa.com

Telephone (201) 933-8800

Telefax (201) 804-1076

Emergency telephone CHEMTREC: 800-424-9300

INTERNATIONAL: 703-527-3887

ehs@sika-corp.com

Recommended use of the chemical and restrictions on

use

For further information, refer to the product technical data

sheet.

2. Hazards identification

GHS Classification

Eye irritation, Category 2A Skin sensitization, Category 1 Carcinogenicity, Category 1A

H319: Causes serious eye irritation.

H317: May cause an allergic skin reaction.

H350: May cause cancer.

GHS Label element

Hazard pictograms





Signal Word

Hazard Statements : H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H350 May cause cancer.

Precautionary Statements : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of

the workplace.

P280 Wear eye protection/ face protection.

P280 Wear protective gloves.

P281 Use personal protective equipment as required.



Revision Date 04/29/2015

Print Date 04/29/2015

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/

P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

See Section 11 for more detailed information on health effects and symptoms.

There are no hazards not otherwise classified that have been identified during the classification process.

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

3. Composition/information on ingredients

Hazardous ingredients

Chemical Name	CAS-No.	Concentration (%)
Quartz (SiO2)	14808-60-7	>= 25 - < 50 %
dibenzoyl peroxide	94-36-0	>= 10 - < 20 %
Quartz (SiO2) <5µm	14808-60-7	< 1 %

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Induce vomiting immediately and call a physician.



Revision Date 04/29/2015

Print Date 04/29/2015

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed

: Allergic reactions Excessive lachrymation

See Section 11 for more detailed information on health effects

and symptoms.

irritant effects sensitizing effects carcinogenic effects

May cause an allergic skin reaction. Causes serious eye irritation.

May cause cancer.

Protection of first-aiders : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in

attendance.

Notes to physician : Treat symptomatically.

5. Fire-fighting measures

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Specific extinguishing

methods

: Use water spray to cool unopened containers.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for fire-fighters

: In the event of fire, wear self-contained breathing apparatus.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Environmental precautions : Use personal protective equipment. Deny access to unprotected persons.

: Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.



Revision Date 04/29/2015

Print Date 04/29/2015

7. Handling and storage

Advice on safe handling : Do not breathe vapors or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is

being used.

Smoking, eating and drinking should be prohibited in the

application area.

Follow standard hygiene measures when handling chemical

products.

Conditions for safe storage : Prevent unauthorized access.

Store in original container.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Observe label precautions.

Store in accordance with local regulations.

Materials to avoid : No data available

8. Exposure controls/personal protection

Component	CAS-No.	Basis **	Value	Exposure limit(s)* / Form of exposure
Glycerol	56-81-5	OSHA P0	TWA	10 mg/m3 Total
		ACGIH	TWA	10 mg/m3
Quartz (SiO2)	14808-60-7	ACGIH	TWA	0.025 mg/m3 Respirable fraction
		OSHA Z-3	TWA	30 mg/m3 / %SiO2+2 total dust
		OSHA Z-3	TWA	10 mg/m3 / %SiO2+2 respirable
		OSHA Z-3	TWA	250 mppcf / %SiO2+5 respirable
		OSHA P0	TWA	0.1 mg/m3



Revision Date 04/29/2015

Print Date 04/29/2015

				Respirable fraction
		OSHA P0	TWA	0.1 mg/m3 respirable dust fraction
		ACGIH	TWA	0.025 mg/m3 Respirable fraction
		ACGIH	TWA	0.025 mg/m3 Respirable fraction
dibenzoyl peroxide	94-36-0	ACGIH	TWA	5 mg/m3
		OSHA Z-1	TWA	5 mg/m3
		OSHA P0	TWA	5 mg/m3
Quartz (SiO2) <5µm	14808-60-7	ACGIH	TWA	0.025 mg/m3 Respirable fraction
		OSHA Z-3	TWA	30 mg/m3 / %SiO2+2 total dust
		OSHA Z-3	TWA	10 mg/m3 / %SiO2+2 respirable
		OSHA Z-3	TWA	250 mppcf / %SiO2+5 respirable
		OSHA P0	TWA	0.1 mg/m3 Respirable fraction
		OSHA PO	TWA	0.1 mg/m3 respirable dust fraction
		ACGIH	TWA	0.025 mg/m3 Respirable fraction
		ACGIH	TWA	0.025 mg/m3 Respirable fraction



Revision Date 04/29/2015

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

**Basis

ACGIH. Threshold Limit Values (TLV)

OSHA Po. Table Z-1, Limit for Air Contaminat (1989 Vacated Values)

OSHA P1. Permissible Exposure Limits (PEL), Table Z-1, Limit for Air Contaminant

OSHA P2. Permissible Exposure Limits (PEL), Table Z-2

OSHA Z3. Table Z-3, Mineral Dust

Engineering measures : Use of adequate ventilation should be sufficient to control

worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any

recommended or statutory limits.

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed

respirator complying with an approved standard if a risk

assessment indicates this is necessary.

The filter class for the respirator must be suitable for the

maximum expected contaminant concentration

(gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained

breathing apparatus must be used.

Hand protection

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is

necessary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling the

product.

Remove contaminated clothing and protective equipment

before entering eating areas. Wash thoroughly after handling.

9. Physical and chemical properties

Safety Data Sheet

Sikadur AnchorFix®-1 Part B



Revision Date 04/29/2015

Appearance : liquid
Color : various

Odor : slight

Odor Threshold : No data available

Flash point : Note: Not applicable

Ignition temperature : Not applicable

Decomposition temperature : No data available

Lower explosion limit (Vol%) : No data available

Upper explosion limit (Vol%) : No data available

Flammability (solid, gas) : No data available

Oxidizing properties : No data available

Autoignition temperature : No data available

pH : No data available

Melting point/range /

Freezing point

Density

Boiling point/boiling range : No data available

Vapor pressure : No data available

at 68 °F (20 °C)

: No data available

Partition coefficient: n-

octanol/water

Water solubility

Viscosity, dynamic

: No data available

ca.1.55 g/cm3

No data available

: No data available

Viscosity, kinematic : > 20.5 mm2/s

at 104 °F (40 °C)

Relative vapor density : No data available

Evaporation rate : No data available

Burning rate : No data available

Volatile organic compounds

(VOC) content

36 g/I A+B Combined



Revision Date 04/29/2015

Print Date 04/29/2015

10. Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous

reactions

: Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

11. Toxicological information

Acute toxicity

Not classified based on available information.

Ingredients:

dibenzoyl peroxide:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

: LC50 (Rat): > 24.3 mg/l Acute inhalation toxicity

Exposure time: 4 h

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization: May cause an allergic skin reaction.

Respiratory sensitization: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer.

IARC Group 1: Carcinogenic to humans

> Quartz (SiO2) 14808-60-7

> Quartz (SiO2) <5µm 14808-60-7

Known to be human carcinogen NTP

> Quartz (SiO2) 14808-60-7 Quartz (SiO2) <5µm 14808-60-7

Reproductive toxicity

Not classified based on available information.



Revision Date 04/29/2015

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Aspiration toxicity

Not classified based on available information.

12. Ecological information

Other information Do not empty into drains; dispose of this material and its

container in a safe way.

Avoid dispersal of spilled material and runoff and contact

with soil, waterways, drains and sewers.

Toxic to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

May be harmful to the environment if released in large

quantities.

Water polluting material.

13. Disposal considerations

Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

14. Transport information

DOT

Not regulated

IATA

UN number 3082

Description of the goods Environmentally hazardous substance, liquid, n.o.s.

(dibenzoyl peroxide, nonylbenzoate, branched and linear)

Class 9
Packing group III
Labels 9
Packing instruction (cargo 964

aircraft)

Packing instruction 964

Safety Data Sheet

Sikadur AnchorFix®-1 Part B



Revision Date 04/29/2015

0 1/20/20 1 C

(passenger aircraft)
Packing instruction

Y964

(passenger aircraft)

IMDG

UN number 3082

Description of the goods ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(dibenzoyl peroxide, nonylbenzoate, branched and linear)

Class 9
Packing group III
Labels 9
EmS Number 1 F-A
EmS Number 2 S-F

Marine pollutant yes

IMDG: For Limited Quantity special provisions reference IMDG Code Chapter 3.4

Special precautions for user

No data available

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

15. Regulatory information

TSCA list : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA304 Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Acute Health Hazard

Chronic Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

 dibenzoyl peroxide
 94-36-0
 15.00 %

 zinc distearate
 557-05-1
 3.00 %



Revision Date 04/29/2015

Print Date 04/29/2015

Clean Air Act

Ozone-Depletion Potential

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act

Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

California Prop 65

WARNING! This product contains a chemical known in the

State of California to cause cancer.

16. Other information

HMIS Classification



Caution: HMIS® rating is based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® rating is not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® rating is to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). Please note HMIS® attempts to convey full health warning information to all employees.

Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 04/29/2015

Safety Data Sheet

Sikadur AnchorFix®-1 Part B



Revision Date 04/29/2015

Material number: 426081