

# Sikadur Combiflex Kit - Part A

#### HMIS

HEALTH	2
FLAMMABILITY	1
REACTIVITY	0
PERSONAL PROTECTION	С

# 1. Product And Company Identification

Supplier
Sika Corporation
201 Polito Ave
Lyndhurst, NJ 07071

Company Contact: EHS Department Telephone Number: 201-933-8800 FAX Number: 201-933-9379 Web Site: www.sikausa.com

**Supplier Emergency Contacts & Phone Number** 

CHEMTREC: 800-424-9300 INTERNATIONAL: 703-527-3887 Manufacturer
Sika Corporation
201 Polito Ave
Lyndhurst, NJ 07071

Company Contact: EHS Department Telephone Number: 201-933-8800 FAX Number: 201-933-9379 Web Site: www.sikausa.com

**Manufacturer Emergency Contacts & Phone Number** 

CHEMTREC: 800-424-9300 INTERNATIONAL: 703-527-3887

Issue Date: 02/18/2004

Product Name: Sikadur Combiflex Kit - Part A

CAS Number: Not Established

Chemical Family: Modified Epoxy Resin

MSDS Number: 3089 Product Code: 0390130

# 2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
AROMATIC HYDROCARBON BLEND	Trade Secret	
CALCIUM CARBONATE	471-34-1	
MODIFIED EPOXY RESIN	Trade Secret	
NONYLPHENOL	25154-52-3	
SILICA, QUARTZ	14808-60-7	

Note: Exposure to silica, quartz is applicable only if cured with Part "B" and sanded.

#### 3. Hazards Identification

# **Eye Hazards**

May cause eye irritation.

# **Skin Hazards**

May cause skin irritation. May cause skin sensitization.

# Sikadur Combiflex Kit - Part A

#### 3. Hazards Identification - Continued

# **Ingestion Hazards**

Harmful if swallowed.

#### **Inhalation Hazards**

May cause nose, throat, and lung irritation.

#### 4. First Aid Measures

# E<u>ye</u>

Rinse eyes thoroughly with water for at least 15 minutes. Consult physician.

# <u>Skin</u>

In case of contact, immediately flush skin with plenty of water for at least 15 minutes.

## <u>Ingestion</u>

Dilute with water. If swallowed, do not induce vomiting unless directed to do so by medical personnel.

#### Inhalation

If not breathing, give artificial respiration, seek medical attention.

# 5. Fire Fighting Measures

Flash Point: >213 °F >101 °C

#### Fire And Explosion Hazards

None Known.

#### **Extinguishing Media**

In case of fire, use water spray (fog) foam, dry chemical, or CO2.

# **Fire Fighting Instructions**

Firefighters should wear self-contained breathing apparatus and full protective gear.

#### 6. Accidental Release Measures

Avoid release to the environment. Use appropriate personal protective equipment (PPE). Contain spill and collect with absorbent material and transfer into suitable containers. Ventilate enclosed area.

# 7. Handling And Storage

#### **Handling And Storage Precautions**

Store in a cool area. Keep containers tightly closed. Keep awat from ignition sources. Protect from heat and direct sunlight.

# **Work/Hygienic Practices**

Wash thoroughly with soap and water after handling.

# 8. Exposure Controls/Personal Protection

#### **Engineering Controls**

Use with adequate general and local exhaust ventilation.

#### **Eye/Face Protection**

Safety glasses with side shields or goggles.

# **Skin Protection**

Chemical-resistant gloves. Lab coat or other work clothing to prevent skin exposure. Launder before reuse.

#### **Respiratory Protection**

A respirator protection program that meets 29 CFR 1910.134 requirement must be followed whenever workplace conditions warrant a respirator's use. In areas where the Permissible Expsoure Limits are exceeded, use a

# Sikadur Combiflex Kit - Part A

## 8. Exposure Controls/Personal Protection - Continued

# **Respiratory Protection - Continued**

properly fitted NIOSH-approved respirator.

#### **Other/General Protection**

Wash thoroughly after handling.

#### Ingredient(s) - Exposure Limits

**CALCIUM CARBONATE** 

ACGIH TLV-TWA 10 mg/m3

OSHA PEL-TWA 15 mg/m3

OSHA PEL-TWA 5 mg/m3

SILICA, QUARTZ

ACGIH TLV-TWA 0.1 mg/m3 (Notice of Intended Change)

ACGIH TLV-TWA 0.05 mg/m3 (Proposed)

OSHA PEL-TWA 30/%SiO2+2 mg/m3

OSHA PEL-TWA 10/%SiO2+2 mg/m3

OSHA PEL-TWA 250/%SiO+5 mppcf

# 9. Physical And Chemical Properties

#### **Appearance**

Yellowish Liquid

# Odor

Characteristic

Chemical Type: Mixture Physical State: Liquid Packing Density: 1.1 g/cm3

Solubility: Insoluble

Evaporation Rate: Slower than ether

## 10. Stability And Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur

## **Conditions To Avoid (Stability)**

None known

#### **Incompatible Materials**

None when stored and handled according to prescribed instruction.

#### 11. Toxicological Information

## **Eye Effects**

Irritation

#### **Skin Effects**

Sensitization/allergic reaction possible.

#### **Conditions Aggravated By Exposure**

Eye disease, skin disorders and allergies, chronic respiratory disease

# Ingredient(s) - Carginogenicity

SILICA, QUARTZ

NTP - Listed On The National Toxicology Program

Listed In The IARC Monographs

# Sikadur Combiflex Kit - Part A

## 12. Ecological Information

Do not allow to enter waste water drians, waterways, or soil.

# 13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations.

# 14. Transport Information

#### **Proper Shipping Name**

Not regulated by the USDOT.

# 15. Regulatory Information

# **U.S. Regulatory Information**

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

# **SARA Hazard Classes**

Acute Health Hazard Chronic Health Hazard

# **SARA Section 313 Notification**

This product does not contain any ingredients regulated under Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 or 40 CFR 372.

# **State Regulations**

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects, or other reproductive harm.

#### Ingredient(s) - State Regulations

**CALCIUM CARBONATE** 

Pennsylvania - Workplace Hazard

NONYLPHENOL

Pennsylvania - Workplace Hazard

Massachusetts - Hazardous Substance

SILICA, QUARTZ

New Jersey - Workplace Hazard

Pennsylvania - Workplace Hazard

California - Proposition 65

Massachusetts - Hazardous Substance

## 16. Other Information

# **HMIS Rating**

Health: 2 Fire: 1 Reactivity: 0 PPE: C

# Revision/Preparer Information MSDS Preparer: EHS Department

MSDS Preparer Phone Number: 201 933 8800

This MSDS Supercedes A Previous MSDS Dated: 04/15/2003

# Sikadur Combiflex Kit - Part A

#### **Disclaimer**

The data in this Material Safety Data Sheet relates only to the specific material herein and does not relate to use in combination with any other material or in any process. The information set forth herein is based on technical data that Sika believes to be reliable as of the date hereof. Since conditions of use are outside our control, we make no warranties, express or implied and assume no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under or a recommendation to infringe any patents.

# SIKA CORPORATION

Printed Using MSDS Generator™ 2000