

SIKASIL COLORPACK (All Colors)

SECTION 1 - Product and Company Identification

PRODUCT NAME: SIKASIL COLORPACK (All Colors)

PRODUCT CODE: SIKASIL COLORPACK (All Colors), Silicone Sealant

ADDRESS: Sika Corporation

201 Polito Avenue Lyndhurst, NJ 07071

PHONE: (201) 933 - 8800 FAX: (201) 804 - 1076

EMERGENCY PHONE: (CHEMTREC) (800) 424 9300

International (CHEMTREC) (703) 527-3887

REVISION DATE : 12/20/10 SUPERSEDES: 12/03/08

SECTION 2 - COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

This product consists of a mixture/preparation. Due to its final form, the ingredients in this product are not considered hazardous per the OSHA Hazard Communication Standard. Under normal conditions of use, no respirable particles are released from this product.

SECTION 3 - HAZARDS IDENTIFICATION

MAIN SYMPTOMS:

EYE: Direct contact causes slight eye irritation.

SKIN: Exposure may irritate mildly.

INHALATION: Overexposure may cause respiratory tract irritation.

ORAL: Swallowing may cause digestive discomfort and gastrointestinal irritation.

HMIS HAZARD CODES: Health: 1 Flammability: 1 Reactivity: 0 PPE: C

SECTION 4 - FIRST-AID PROCEDURES

INHALATION: Remove to fresh air. If ill effects persist, get medical attention.

SKIN CONTACT: Remove from skin and immediately flush with water for 15 minutes. Get medical attention if irritation develops

or ill effects persist.

EYE CONTACT: Immediately flush with water for 15 minutes. Get medical attention.

INGESTION: Get medical attention.

COMMENTS: Treat according to person's condition and specifics of exposure.

SECTION 5 - FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Compatible with all usual extinguishing media

FIRE FIGHTING PROCEDURES: Wear full protective clothing, positive pressure or pressure demand breathing apparatus

and protective covering for exposed areas of the head. If large amount is involved,

evacuate area.

FLASH POINT (SETAFLASH): HAZARDOUS DECOMPOSITION

Greater than 100°C (212°F)

PRODUCTS:

By high heat and fire: oxides of carbon.



SIKASIL COLORPACK (All Colors)

SECTION 6 - ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Observe all personal protective equipment recommendations described in Sections 5 and 8. **ENVIRONMENTAL PRECAUTIONS:** Disposal of collected product, residues, and cleanup materials may be governmentally

regulated. Observe all applicable local, state and federal waste management regulations.

METHODS FOR CLEANING UP:

Ventilate area. Extinguish all ignition sources. Contain spill. Evacuate unprotected personnel from hazard area. Cover with absorbent, place in approved drum; do not seal drum for 48 hours to avoid possible pressure build-up. Local, state, and federal reporting requirements may apply to spills or releases of this material into the environment. See applicable regulatory compliance

information in Section 15.

SECTION 7 - HANDLING AND STORAGE

Assure good ventilation HANDLING:

STORAGE: Eliminate sources of ignition. Store in original sealed containers away from heat and moisture.

SECTION 8 - EXPOSURE CONTROL AND PERSONAL PROTECTION

ENGINEERING CONTROLS:

LOCAL EXHAUST: Recommended **GENERAL VENTILATION:** Recommended

PERSONAL PROTECTIVE EQUIPMENT:

EYE PROTECTION: Avoid eye contact. Use proper protection - safety glasses recommended.

SKIN AND BODY PROTECTION: Avoid skin contact. Protect hands with impervious rubber gloves and wear typical full cover

clothing.

RESPIRATORY PROTECTION: Wear appropriate, properly fitted NIOSH/MSHA approved respirator while the product is

mixed and when the airborne contaminant levels exceed the exposure limits in poorly

ventilated areas.

Follow respirator manufacturer's directions for respirator use.

HYGIENE MEASURES (INGESTION):

Wash hands after handling and before eating.

PRECAUTIONARY MEASURES: Avoid eye contact. Avoid skin contact. Avoid breathing vapor. Keep container closed. Do

not take internally.

Note: These precautions are for room temperature handling. Use at elevated temperatures or in aerosol spray applications may require added precautions.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL FORM: Solid (Paste) ODOR: Slight odor VAPOR PRESSURE (AT 100°F): Not applicable

DENSITY: NA SOLUBILITY IN WATER (%): NIL SPECIFIC GRAVITY (AT 77°F/25°C): NA

Less than 0.1% % VOLATILE BY VOLUME:

VOLATILE ORGANIC CONTENT (VOC):

FLASH POINT (SETAFLASH): Greater than 100°C (212°F)

NOTE: The above information is not intended for use in preparing product specifications.

SECTION 10 - STABILITY AND REACTIVITY

CHEMICAL STABILITY: HAZARDOUS DECOMPOSITION Stable. No hazardous reactions when stored and handled according to prescribed instructions.

PRODUCTS:

Thermal decomposition products as described in Section 5.



SIKASIL COLORPACK (All Colors)

SECTION 11 - TOXICOLOGICAL INFORMATION

None known.

CHRONIC EXPOSURE:

SKIN: Exposure may irritate mildly.

INHALATION: Overexposure may cause respiratory tract irritation.

ORAL: Swallowing may have adverse effects depending on quantity ingested.

SECTION 12 - ECOLOGICAL INFORMATION

No data available.

SECTION 13 - DISPOSAL INFORMATION

PRODUCT DISPOSAL: RCRA Hazard Class (40 CFR 261)

When a decision is made to discard this material, as received, is it classified as a hazardous waste? NO.

State or local laws may impose additional regulatory requirements regarding disposal.

SECTION 14 - TRANSPORT INFORMATION

DOT Information (49CFR 172.101)

PROPER SHIPPING NAME:

HAZARD CLASS:

Not Applicable

Not Applicable

UN / NA NUMBER: None

PACKING GROUP: Not Applicable

SECTION 15 - REGULATORY INFORMATION

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

US FEDERAL REGULATIONS:

CERCLA/SARA – Hazardous Substances and their Reportable Quantities

Based on an evaluation of the components used, this product does contain hazardous ingredients identified as per 29 CFR 1910.1200.

TOXIC SUBSTANCE CONTROL ACT (TSCA):

TSCA Status: All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.

SARA 302 EXTREMELY HAZARDOUS SUBSTANCES

None

SARA 311/312 HAZARD CATEGORIES:

Immediate: No Delayed: No Fire: No Pressure: No Reactive: No



SIKASIL COLORPACK (All Colors)

Section 313

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right to Know Act:

None

STATE REGULATIONS:

This product does comply with the California Air Resources Board maximum for VOC's in a sealant.

Per the California Air Resources Board TITLE 17 Division 3 Chapter 1 Subchapter 8.5 Article 2 §94508, a VOC is a substance with a vapor pressure greater than or equal to 0.1 mmHg at 20°C (68°F), or is a chemical compound with less than or equal to 12 carbon atoms if the vapor pressure is not known, or is a chemical compound with a boiling point less than or equal to 216°C (421°F).

STATE RIGHT-TO-KNOW REGULATIONS:

States within the US that have promulgated State Right-to-Know regulations with chemical listing requirements including the chemicals in this product are provided below.

Chemical	CAS No.	Wt%	States
5			
Dimethyl siloxane	70131-67-8	>50	New Jersey, New York, Pennsylvania
Carbon Black	1333-86-4	0 – 40	New Jersey, Pennsylvania
Iron Oxide	1309-37-1	0 - 40	New Jersey, Massachusetts, Pennsylvania
Titanium Dioxide	13463-67-7	0 - 40	New Jersey, Massachusetts, Pennsylvania
Aluminum	7429-90-5	0 - 40	New Jersey, Massachusetts, Pennsylvania
CI Pigment Blue	57455-37-5	0 - 40	New Jersey, Pennsylvania
Yellow Iron Oxide	51274-00-1	0 - 40	New Jersey, Pennsylvania

INTERNATIONAL:

Canada

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

Canadian DSL

All ingredients in this product are currently listed on the Canadian Domestic Substances List (DSL). The substances that are on the DSL would not be considered new for the purposes of the Canadian Environmental Protection Act (CEPA).

Note:

The recipient of this product should be aware of the possible existence of additional local regulations, which may be applicable to this product.

SECTION 16 - OTHER INFORMATION

The information contained in this Material Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Technical Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THISINFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL ORCONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN AMANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BYOTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikacorp.com or 201-933-8800.