Sika®

MATERIAL SAFETY DATA SHEET

Page 1 of 4

Sikatop 111 Plus/121 Plus/122 Plus/123 Plus/126 Plus - Part A

HMIS

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION [С

1. Product And Company Identification

Supplier
Sika Corporation

201 Polito Ave Lyndhurst, NJ 07071

Company Contact: EHS Department Telephone Number: 201-933-8800 FAX Number: 201-933-9379 Web Site: www.sikausa.com

Supplier Emergency Contacts & Phone Number

CHEMTREC: 800-424-9300 INTERNATIONAL: 703-527-3887 Manufacturer
Sika Corporation
201 Polito Ave
Lyndhurst, NJ 07071

Company Contact: EHS Department Telephone Number: 201-933-8800 FAX Number: 201-933-9379 Web Site: www.sikausa.com

Manufacturer Emergency Contacts & Phone Number

CHEMTREC: 800-424-9300 INTERNATIONAL: 703-527-3887

Issue Date: 04/26/2004

Product Name: Sikatop 111 Plus/121 Plus/122 Plus/123 Plus/126 Plus - Part A

MSDS Number: 3155 Product Code: Various

Synonyms

SIKATOP 111 PLUS - PART A SIKATOP 121 PLUS - PART A SIKATOP 122 PLUS - PART A SIKATOP 123 PLUS - PART A SIKATOP 126 PLUS - PART A

2. Composition/Information On Ingredients

This products contains no hazardous ingredients when evaluated by criteria established in the OSHA Hazard Communication Standard (29 CFR 1910.1200).

3. Hazards Identification

Eye Hazards

May cause eye irritation.

Skin Hazards

May cause skin irritation.

Ingestion Hazards

May be harmful if swallowed.

Inhalation Hazards

Moderate respiratory irritant.

Sikatop 111 Plus/121 Plus/122 Plus/123 Plus/126 Plus - Part A

4. First Aid Measures

Eye

In case of contact, hold eyelids apart and immediately flush eyes with plenty of tepid water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

Skin

In case of contact, immediately flush skin with soap and plenty of tepid water for at least 15 minutes. Get medical attention immediately if irritation (redness, rash, blistering) develops and persists.

Ingestion

If victim is fully conscious, give one or two cups of water or milk to drink. Call a physician if necessary.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration. Call a physician if needed.

5. Fire Fighting Measures

Flash Point: >220 °F

Fire And Explosion Hazards

Material may splatter above 212F. Polymer film can burn.

Extinguishing Media

In case of fire, use water spray (fog) foam, dry chemical, or CO2.

Fire Fighting Instructions

In the event of a fire, firefighters should wear full protective clothing and NIOSH-approved self-contained breathing apparatus with a full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Avoid release to the environment. Use appropriate Personal Protective Equipment (PPE). Contain spill and collect with absorbent material and transfer into suitable containers. Do not flush to sewer or allow to enter waterways. Ventilate enclosed area.

7. Handling And Storage

Handling And Storage Precautions

Keep out of reach of children. Store in a cool, dry, well ventilated area. Keep containers tightly closed.

Work/Hygienic Practices

Wash thoroughly with soap and water after handling.

8. Exposure Controls/Personal Protection

Engineering Controls

Use with adequate general and local exhaust ventilation. Refer to the current edition of "Industrial Ventilation: A Manual of Recommended Practice" published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

Eye/Face Protection

Faceshield over safety glasses or goggles.

Skin Protection

Wear long sleeve shirt, long pants, chemical resistant gloves.

Respiratory Protection

A respirator protection program that meets 29 CFR 1910.134 requirement must be followed whenever workplace conditions warrant a respirator's use.

Sikatop 111 Plus/121 Plus/122 Plus/123 Plus/126 Plus - Part A

9. Physical And Chemical Properties

Appearance

Green Liquid

Odor

Acrylic smell

Chemical Type: Mixture Physical State: Liquid Percent VOCs: 0%

Packing Density: 8.5 pounds/gallon

Vapor Density: >AIR

Evaporation Rate: Slower then ether

10. Stability And Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur

Conditions To Avoid (Stability)

Avoid Freezing

Incompatible Materials

None Known

Hazardous Decomposition Products

None Known

Conditions To Avoid (Polymerization)

None Known

11. Toxicological Information

Conditions Aggravated By Exposure

None Known

12. Ecological Information

No Data Available...

13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations. Waste generators must determine whether a discarded material is classified as a hazardous waste. USEPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

14. Transport Information

Proper Shipping Name

Not Regulated by the USDOT.

15. Regulatory Information

U.S. Regulatory Information

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

SARA Section 313 Notification

This product does not contain any ingredients regulated under Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 or 40 CFR 372.

Sikatop 111 Plus/121 Plus/122 Plus/123 Plus/126 Plus - Part A

16. Other Information

HMIS Rating
Health: 1
Fire: 0
Reactivity: 0
PPE: C

Revision/Preparer Information

MSDS Preparer: EHS Department

This MSDS Supercedes A Previous MSDS Dated: 12/16/2003

Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).

SIKA CORPORATION

Printed Using MSDS Generator™ 2000